

PTFE Fiberglass Adhesive Tape

PTFE-coated fiberglass tape with silicone adhesive for heat-seal bars and jaws. Brown, white or black. -70 to 260 °C, residue-free.



Temperature range	-70 to 260 °C (-94 to 500 °F)
Adhesive	Silicone
Properties	Waterproof, non-stick, residue-free
Brand	FireHush
Base SKU	FH-PTT

About this product

The standard tape for covering heat-seal bars, impulse sealer jaws and hot rollers. Silicone adhesive, removes clean. Six thicknesses from 0.13 to 0.30 mm total.

Specifications by model

Model	Fabric mm	Total mm	Adhesion N/5 cm (brown, white)	Adhesion N/5 cm (black)
PT008AS	0.08	0.13	600/500	540/480
PT012AS	0.11	0.16	1100/1000	950/750
PT013AS	0.13	0.18	1150/1050	1000/800
PT015AS	0.15	0.20	1300/1200	1200/1100
PT018AS	0.18	0.23	1600/1400	1500/1300
PT025AS	0.25	0.30	2200/1700	2100/1600

Options and SKUs

SKU	Model	Color
FH-PTT-PT008AS-BRN	PT008AS (0.13 mm)	Brown

SKU	Model	Color
FH-PTT-PT008AS-WHT	PT008AS (0.13 mm)	White
FH-PTT-PT008AS-BLK	PT008AS (0.13 mm)	Black
FH-PTT-PT012AS-BRN	PT012AS (0.16 mm)	Brown
FH-PTT-PT012AS-WHT	PT012AS (0.16 mm)	White
FH-PTT-PT012AS-BLK	PT012AS (0.16 mm)	Black
FH-PTT-PT013AS-BRN	PT013AS (0.18 mm)	Brown
FH-PTT-PT013AS-WHT	PT013AS (0.18 mm)	White
FH-PTT-PT013AS-BLK	PT013AS (0.18 mm)	Black
FH-PTT-PT015AS-BRN	PT015AS (0.20 mm)	Brown
FH-PTT-PT015AS-WHT	PT015AS (0.20 mm)	White
FH-PTT-PT015AS-BLK	PT015AS (0.20 mm)	Black
FH-PTT-PT018AS-BRN	PT018AS (0.23 mm)	Brown
FH-PTT-PT018AS-WHT	PT018AS (0.23 mm)	White
FH-PTT-PT018AS-BLK	PT018AS (0.23 mm)	Black
FH-PTT-PT025AS-BRN	PT025AS (0.30 mm)	Brown
FH-PTT-PT025AS-WHT	PT025AS (0.30 mm)	White
FH-PTT-PT025AS-BLK	PT025AS (0.30 mm)	Black

Test reports

A test report for this item is available on request from the manufacturer. Ask us for a copy before you buy for a regulated site.

Safety notes

- Ask for widths and roll lengths.

Custom sizes, colors, packaging and logo printing are available on volume orders.